



ULTRAFLEX 40



FEATURES

ULTRAFLEX 40 Sheet Rubber is a pink, highly elastic premium grade 40 Duro natural rubber specifically designed to display excellent resistance to cutting, tearing and abrasion.

ULTRAFLEX 40 is suitable for both wet and dry fine particle abrasion applications.

ULTRAFLEX 40 is generally mechanically fastened or can be buffed for bonding to steel surfaces. Once buffed, it can be used with many 2-part Neoprene based lining glues.

APPLICATIONS

ULTRAFLEX 40 has been designed for use in a variety of different wear applications including:

- ✓ Chute and screen lining
- ✓ Premium skirting rubber
- ✓ Conveyor curtains
- ✓ Transfer socks
- ✓ Pipe repair bandage
- ✓ Gasket and seals
- ✓ Variety of sealing applications

Polymer	NR	
Colour	Pink with smooth back	
Specific Gravity	1.05	ASTM D297
Hardness	40° ± 5° Shore A	ASTM D2240
Abrasion	95 mm ³ (max) @ 5N	ASTM D5963
Tensile Strength	18 MPa (min)	ASTM D412
Elongation @ Break	550% (min)	ASTM D624
Tear Strength	60 N/mm (min)	
Temperature Range	-20°C +20°C	